



NEW XCMG DUMP TRUCK SERIES

XT400DT 6x4 DUMP TRUCK

SPECIFICATION XCMG XT400DT 6x4 XGA3251D2WC



CABIN

Type	Hanvan G7
Seats	2

PERFORMANCE

Drive type	6x4
Curb Weight (kg)	17.040
Gross Vehicle Weight - GVW (kg)	41.500
Max.Speed (Km/h)	78
Min.Turning Radius (m)	20
Max.Gradeability (%)	39
Fuel Tank Capacity (Liter)	400

TRANSMISSION

Model	10JSD180T
PTO	QH50
Forward Gear Ratio	14.98 - 1.00
Reverse Gear Ratio	15.113 / 3.377

CLUTCH

Type	Dry type, single plate, pull type diaphragm spring clutch, hydraulic controlled and air auxiliary power supply.
Driven Plate Diameter (mm)	Ø430

FRONT AXLE

Capacity	9.5T
Brake type	Drum Type

DRIVEN AXLE

Capacity	2 x 16T Hub reduction
Ratio	5,921
Brake type	Drum Type

FRAME

Type	Groove straight beam
Main Rail Section (mm)	320 x 90 x (8+8)
Width of chassis structure	865

DIFFERENTIAL LOCK

Inter Axle Differential Lock	Yes
Inter Wheel Differential Lock	Yes

BRAKE SYSTEM

Driving Brake	Dual circuit pneumatic braking & Drum type
Parking Brake	Spring energy storage typ
Auxiliary Brake	Exhaust brake & Engine brake

ELECTRICAL SYSTEM

Voltage (V)	24
Battery Voltage & Capacity (V/Ah)	2 x 12/165



Driver's seat with Air Suspension system for driver's comfort with cooler and electrical adjuster.



Air Conditioner system with automatic control, audio system and USB Port.



Steer system with Power Steering, Tilt Steering Wheel and Spacious Cabin.

ENGINE

Model	SC12E400Q3
Displacement	11.800 cc
Max. Output Power	294kW / 400Hp
Max. Torque	1.600Nm / 1.400 Rpm
Standard Emission	Euro 2

SUSPENSION

Front	Type	Multi Spring
	Amount of spring plate	10
Rear	Type	Multi Spring
	Amount of spring plate	12

DIMENSIONS

Overall Dimensions (mm)	Length	8.990
	Weight	2.250
	Height	3.590
Wheelbase (mm)	4.200 + 1.450	
Min.Ground Clearance (mm)	281	
Approach Angle (°)	17°	
Departure Angle (°)	25°	
Front Overhang - FO (mm)	1.500	
Rear Overhang - RO (mm)	1.938	

CARGO SIZE

Diameter L x W x H (mm)	Scow End	5.800 x 2.500 x 1.450
	Tail Gate	6.200 x 2.400 x 1.900

OPTION WHEEL

Rim	8.0 - 20	
Tyre	Model	12.00R20 18PR
	Air Pressure (Psi)	125 ± 10
Rim	8.5 - 24	
Tyre	Model	12.00R24 18PR
	Air Pressure (Psi)	125 ± 10

*The specification can change without prior notice. Performance data depend on operational conditions.

OFFICIAL NETWORK

-Head Office Jakarta -Aceh -Medan -Pekanbaru -Jambi -Palembang -Lampung -Bekasi -Cirebon -Cilegon -Semarang -Surabaya -Banjarasin -Balikpapan -Samarinda -Pontianak
-Manado -Palu -Makassar -Kendari -Sorong -Jayapura



PT PANCA MEGA MAKMUR

Komp. Jakarta Distribution Centre Pluit Bisnis F1 No.9 RT.001 RW.002
Kamal Muara, Penjaringan, Jakarta Utara 14470

Dealer :